

Brolac Wood Varnish Stain

DESCRIPTION: A premium quality varnish based on modified alkyd containing high-grade ingredients to provide a tough, durable and hardwearing-pigmented wood finishes. It has excellent flow and film build-up.

SCOPE: Designed for use on exterior and interior timber to enhance the wood appearance with deep rich natural colours with gloss. Can be use as a highly decorative varnish for interior and exterior timber.

COMPOSITION: Polyurethane modified alkyd based, Lead Free.

FINISH: Rich Gloss - Excellent appearance to enhance the natural beauty of timber.

COLOUR: Teak, Mahogany, Light Oak, Dark Oak, Medium Oak and Walnut

DRYING TIME Surface dry – 2 to 4 hours.
Touch dry – 7 to 8 hours.
Hard dry – 12 to 14 hours.
Re-coatable – after 12 to 14 hours.
Checked at 25°C and relative humidity not more than 75%.

SPECIFIC GRAVITY: 0.88 ± 0.02 Kgs/L

% VOLUME SOLIDS: 40 ± 2

SPREADING RATE: 12 – 14 m² /L (Depending on surface condition and absorbcency)

THINNER / CLEAN UP: White Spirit. Clean the equipment immediately after use.

FLASH POINT: 37 °C

PACK SIZE: 500 mls and 250 mls

APPLICATION: Brush or spray.

SURFACE PREPARATION: 1.1. NEW WORK
Ensure wood is dry. Sand with fine abrasive paper, dust off. Brush Brolac Wood Varnish Stain in the direction of the grain to avoid patchiness. For best results, two thin coats are recommended instead of one thick coat. Thinning with White Spirit will lighten the shade of the stain.

1.2. OLD WORK

Previously varnished wood of good condition may be re-varnished after light sanding to aid adhesion. Areas such as skirting boards which may be contaminated with wax polish must be degreased with strong detergent solution and allowed to dry thoroughly before painting. When dry, smooth down with fine abrasive paper and apply one full coat of Wood Varnish Stain.

In case of previously varnished wood of damaged condition, the old varnish should be removed with paint remover followed by painting procedure for new wood.

NOTES:	Application of multiple coats will darken the shade. The grain, type and condition of wood will contribute to shade results.	
--------	---	--

STORAGE:	Store in cool, dry condition away from sunlight.	
----------	--	--

DISPOSAL:	Dispose as normal paint. In case of doubt, consult local authority. Do not empty into drains, sewers or other watercourses.	
-----------	--	--

SHELF LIFE:	2 Years, when stored in original condition.	
-------------	---	--

SAFETY PRECAUTIONS:	Ensure adequate ventilation in confined areas where the product is being applied. Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands. Do not breathe spray mist.	
---------------------	---	--

FIRST AID:	EYES	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
	SKIN	Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.
	INHALATION	Remove into fresh air, loosen collar, and avoid excessive exertion.
	INGESTION	In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

DISCLAIMER:

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.



Manufactured by BERGER PAINTS (MALTA) LTD.
HF66, INDUSTRIAL ESTATE, HAL FAR BGG 06
MALTA - EUROPE
TEL: +356 2165 8855 / +356 2165 2996
FAX: +356 2165 9409
EMAIL: info@berger.com.mt
WEBSITE: www.berger.com.mt